

PRODUCT INFORMATION JAMES EXTRA GLOSS

Purpose

- Sealing elastic floors like (structure) vinyl, PVC, linoleum, rubber, PVC and ceramic tiles, natural stone and artificial stone
- Long lasting transparent and glossy protection for (heavy duty) elastic and stone floors

Features

- Completely removable, high gloss protection layer
- Provides a flexible, slip and scratch resistant protection
- Makes suitable floors soil repellent and facilitates daily maintenance
- pH value 8,5

Instructions for use

- Clean the floor thoroughly using James Basic Cleaner. Then, wipe the floor using clean water and leave to dry completely
- Pour James Extra Gloss undiluted into a clean bucket. Then apply, using a clean, good moisture absorbing and lint free cotton cloth, James Extra Gloss thin and evenly on the floor. Do not apply James Extra Gloss directly from the bottle onto the floor (to prevent spotting)
- Leave the floor to dry completely (dependent on the weather, at least 4 hours) and repeat the process
- Intensively used floors need to be treated three times
- Prevent the creation of foaming in the cotton cloth whilst applying James Extra Gloss

Notes

- The floor may be used after James Extra Gloss has hardened, this takes about 12 hours. Only then, furniture may be put back in place. The protection layer is completely hardened after \pm 5 days
- James Extra Gloss can be fully removed using James Basic Cleaner
- Treated floors can subsequently be daily maintained and cleaned perfectly with for instance James Floor Cleaner Clean & Quick dry

Dosage

- Undiluted: per wax layer about 1 l / 20 m²

Detergent Regulation

Phosphates < 5%, BENZISOTHIAZOLINONE, METHYLISOTHIAZOLINONE