



PRODUCT INFORMATION JAMES SEMI GLOSS

FLASK 2 - PROTECTION

Purpose

- Sealing vinyl, PVC, LVT, water resistant laminate, linoleum, marmoleum, rubber, cork, ceramic tiles, natural stone and artificial stone floors
- Long lasting transparent and extra matt protection for floors
- Extends the lifespan of your floor

Features

- For periodic protection
- Completely removable protection layer extends the lifespan of your floor
- Superficial scratches and stripes arise in the protective layer, not in your floor and can thus be restored
- Makes floors soil repellent and simplifies daily maintenance
- Gives your floor an extra matt appearance
- pH value 8,5
- Biodegradable and proudly A.I.S.E. certified

Instructions for use

- To assess the end result, we recommend doing a trial with James Semi Gloss first on a small but relevant area of about 1 m² (follow the instructions and notes below!). In case the end result is to your liking, remove the tested area with James Basic Cleaner according the instructions below
- Clean the floor thoroughly using James Basic Cleaner (flask 1). Then, mop the floor thoroughly using clean water twice (to remove all dirt and Basic Cleaner remnants), and leave to dry completely
- Pour James Semi Gloss undiluted into a clean bucket. Then apply, using a clean, highly absorbent and lint free cotton cloth or wax applicator, James Semi Gloss thin and evenly on the floor. Do not apply James Semi Gloss directly from the bottle onto the floor (to prevent spotting)
- Leave the floor to dry completely (depending on the weather, at least 4 hours)
- Repeat the process by applying a second layer of James Semi Gloss perpendicular to the first layer
- For best results: apply the last layer towards grazing light / window
- Intensively used floors need to be treated two or three times
- Prevent foam and bubble formation in the cotton cloth whilst applying James Semi Gloss

Notes

- Turn off the underfloor heating in time before application
- Ensure adequate ventilation. Avoid drafts and direct sunlight



- The floor may be used once James Semi Gloss has hardened, this takes about 12 hours. Only then, furniture may be put back in place. The protection layer is completely hardened after about 5 days
- James Semi Gloss can be fully removed using James Basic Cleaner
- Protect from frost and extreme temperature drops
- Best when handled with low humidity (< 65%) and normal room temperature (18 - 25° C)
- Treated floors can subsequently be perfectly cleaned and maintained daily using for instance James Floor Cleaner Clean & Quick Dry (flask A)
- Stains on a protective layer (polish) such as James Semi Gloss or James Extra Matt? Spray James Remover directly into a cotton cloth and then use the cloth to gently wipe over the stains. Do **not** let James Remover soak in and immediately rinse with clean water (the protective layer makes it easier to remove stains and this way the protective layer is not (or barely) affected).
- Is James Semi Gloss not matt enough? Use our matter version called James Extra Matt

Dosage

- Undiluted: per wax layer about 1 ltr / 20 m²